

Manual pump for the easy injection of Rewagel Inject 3A+ or Secaugel 90

Application

- Compact manual pump.

Properties

- The injection device has a pressure tank made of stainless steel that can be filled with 5 litres of injection gel.
- This injection device can be used for both Rewagel Inject 3A+ and Secaugel 90.

Directions

- Unscrew the pump and remove it from the tank.
- Pour the bucket of injection gel into the tank's filling opening.
- Reinstall the pump in the tank and screw tight.
- Use the pump to pressure the device to a recommended pressure of 3 bar.
- Remark: For short periods of non-use (less than a week) and when using a seal for the injection rod, the injection gel can be left in the device. For longer periods, the remaining injection gel should be removed from the tank. Rinse the tank afterwards with a mixture of lukewarm water and detergent.

Technical characteristics

- Tank capacity 8,0 L / Filling capacity 5,0 L
- Maximum working pressure 6 bar
- Brass spray lance
- High-efficiency brass pump
- Hose (length 1,35 m)
- Large filling opening for easy filling
- Pressure gauge on tank
- Blow-off / safety valve
- Sturdy quick-acting valve with brass body
- Hose connection at the base (no residual liquid)
- Base ring for stability
- Shoulder strap with padding
- CE mark
- Perbunan (NBR) gaskets

Picture



Packaging
per piece

Safety information – Transport – Handling and storage - Waste

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

Considerations

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.